

Page: 1

Compilation date: 19/3/15

Revision No: 5

# Section 1: Identification of the substance/mixture and of the company/undertaking 1.1. Product identifier Product name: GUN A NAIL EXTRA Product code: SBGAN/SBGANC4 1.2. Relevant identified uses of the substance or mixture and uses advised against 1.3. Details of the supplier of the safety data sheet Company name: EVERBUILD BUILDING PRODUCTS LTD SITE 41, KNOWSTHORPE WAY CROSS GREEN INDUSTRIAL ESTATE LEEDS WEST YORKSHIRE LS9OSW ENGLAND Tel: 0044 113 240 3456 Fax: 0044 113 240 0024 Email: sds@everbuild.co.uk 1.4. Emergency telephone number Emergency tel: 0044 113 240 3456 (office hours only) Manufacturer: EVERBUILD BUILDING PRODUCTS LTD Site 41 Knowsthorpe Way, Cross Green Industrial Estate Leeds West Yorkshire LS9 0SW United Kingdom Tel: (0044) 113 240 3456 Fax: (0044) 113 240 0024 Emergency tel: (0044) 113 240 3456 Email: sds@everbuild.co.uk

# Section 2: Hazards identification

2.1. Classification of the substance or mixture		
Classification under CHIP:	F: R11; -: R52/53; -: R67	
Classification under CLP:	Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Flam. Liq. 2: H225; Skin Irrit. 2: H315	
Most important adverse effects:	Highly flammable. Harmful to aquatic organisms, may cause long-term adverse effects	
	in the aquatic environment. Vapours may cause drowsiness and dizziness.	[oont

GUN A NAIL EXTRA

Hazard statements: H225: Highly flammable liquid and vapour.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H412: Harmful to aquatic life with long lasting effects.

# 2.2. Label elements

Label elements under CLP:

Page: 2

Signal words:	Danger
Hazard pictograms:	GHS02: Flame
	GHS07: Exclamation mark
Precautionary statements:	P102: Keep out of reach of children.
	P501: Dispose of contents to hazardous waste.
	P273: Avoid release to the environment.
	P210: Keep away from heat/sparks/open flames/hot surfaces No smoking.
	P103: Read label before use.
	P243: Take precautionary measures against static discharge.
	P242: Use only non-sparking tools.
	P233: Keep container tightly closed.
	P264: Wash hands thoroughly after handling.
	P280: Wear protective gloves / eye protection.
	P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing.
	Rinse skin with soap and water.
	P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.
	P362: Take off contaminated clothing and wash before reuse.
	P337+313: If eye irritation persists: Get medical advice/attention.
	P403+235: Store in a well-ventilated place. Keep cool.
	P332+313: If skin irritation occurs: Get medical advice.
	P321: Specific treatment (see information on this label).
	P370+378: In case of fire: Use chemical powder, foam or carbon dioxide for extinction.
Label elements under CHIP:	

Label elements under CHIP:

Hazard symbols: Highly flammable.



Risk phrases: R11: Highly flammable.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67: Vapours may cause drowsiness and dizziness.

### GUN A NAIL EXTRA

Safety phrases: S2: Keep out of the reach of children.

S16: Keep away from sources of ignition - No smoking.

S9: Keep container in a well-ventilated place.

S29: Do not empty into drains.

S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.

S43: In case of fire, use dry chemical powder, foam or carbon dioxide.

S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

S46: If swallowed, seek medical advice immediately and show this container or label.

# 2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

**PBT:** This product is not identified as a PBT/vPvB substance.

# Section 3: Composition/information on ingredients

### 3.2. Mixtures

### Hazardous ingredients:

# ETHYL ACETATE - REACH registered number(s): 01-2119475103-46-XXXX

EINECS	CAS	CHIP Classification	CLP Classification	Percent	
205-500-4	141-78-6	F: R11; Xi: R36; -: R66; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319;	10-30%	
			STOT SE 3: H336; -: EUH066		

#### NAPHTHA (PETROLEUM) HYDROTREATED LIGHT

265-151-9	64742-49-0	F: R11; Xi: R38; N: R51/53; Xn: R65; -: R66; -: R67	Flam. Liq. 2: H225; Aquatic Chronic 2: H411; Skin Irrit. 2: H315; STOT SE 3: H336; Asp. Tox. 1: H304	1-10%
NAPHTHA (PE	ETROLEUM), SOL	VENT-REFINED LIGHT - REACH reg	istered number(s): 01-2119473851-33-XXXX	
920-750-0	-	F: R11; Xi: R38; N: R51/53; Xn: R65; -: R66; -: R67	Flam. Liq. 2: H225; Aquatic Chronic 2: H411; Skin Irrit. 2: H315; STOT SE 3: H336; Asp. Tox. 1: H304	1-10%

# Section 4: First aid measures

#### 4.1. Description of first aid measures

Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash
immediately with plenty of soap and water.
Bathe the eye with running water for 15 minutes. Consult a doctor.
Do not induce vomiting. If conscious, give half a litre of water to drink immediately.
Consult a doctor.
Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a
doctor.

Page: 3

#### **GUN A NAIL EXTRA**

Page: 4

4.2. Most important symptoms and effects, both acute and delayed Skin contact: There may be mild irritation at the site of contact. Eye contact: There may be irritation and redness. Ingestion: There may be irritation of the throat. Inhalation: There may be a feeling of tightness in the chest with shortness of breath. 4.3. Indication of any immediate medical attention and special treatment needed Immediate / special treatment: Not applicable. Section 5: Fire-fighting measures 5.1. Extinguishing media Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. 5.2. Special hazards arising from the substance or mixture Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back. 5.3. Advice for fire-fighters Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes. Section 6: Accidental release measures 6.1. Personal precautions, protective equipment and emergency procedures Personal precautions: Refer to section 8 of SDS for personal protection details. Eliminate all sources of ignition. 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

# 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Do not use equipment in clean-up procedure which may produce sparks. Absorb into dry earth or sand.

# 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

# Section 7: Handling and storage

# 7.1. Precautions for safe handling

Handling requirements: Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

### GUN A NAIL EXTRA

# 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed. Keep away from

sources of ignition. Prevent the build up of electrostatic charge in the immediate area.

Ensure lighting and electrical equipment are not a source of ignition.

#### 7.3. Specific end use(s)

Specific end use(s): No data available.

# Section 8: Exposure controls/personal protection

# 8.1. Control parameters

# Hazardous ingredients:

# ETHYL ACETATE

# Workplace exposure limits:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	200 ppm	400 ppm	-	-

**Respirable dust** 

#### **DNEL/PNEC Values**

DNEL / PNEC No data available.

#### 8.2. Exposure controls

Ensure there is sufficient ventilation of the area. Ensure lighting and electrical
equipment are not a source of ignition.
Respiratory protection not required.
Protective gloves. PVA gloves.
Safety glasses. Ensure eye bath is to hand.
Protective clothing.

# Section 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

State:	Liquid		
Colour:	Beige		
Odour:	PETROL-LIKE		
Evaporation rate:	Fast		
Solubility in water:	Insoluble		
Viscosity:	Highly viscous		
Boiling point/range°C:	64	Flash point°C:	-10
Relative density:	~1.25	VOC g/l:	373
<b>A U U</b>			

# 9.2. Other information

Other information: No data available.

# Page: 5

#### **GUN A NAIL EXTRA**

Page: 6

#### Section 10: Stability and reactivity

10.1. Reactivity

#### Reactivity: Stable under recommended transport or storage conditions.

#### 10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

#### 10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

### Section 11: Toxicological information

### 11.1. Information on toxicological effects

### Hazardous ingredients:

### ETHYL ACETATE

DERMAL	RBT	LD50	>20000	mg/kg
ORAL	RAT	LD50	6100	mg/kg
ORAL	RBT	LD50	4934	mg/kg
VAPOURS	RAT	4H LC50	29.3	ppmV

Toxicity values: No data available.

# Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be a feeling of tightness in the chest with shortness of breath.

# Section 12: Ecological information

12.1. Toxicity

#### GUN A NAIL EXTRA

Page: 7

#### Hazardous ingredients:

#### ETHYL ACETATE

Daphnia magna	48H EC50	3090	mg/l
Pimephales promelas (Fat-head Minnow)	96H LC50	230	mg/l

#### 12.2. Persistence and degradability

Persistence and degradability: No data available.

### 12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

# 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

# 12.6. Other adverse effects

Other adverse effects: Harmful to aquatic organisms.

#### Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal

company.

Waste code number: 08 04 09

**NB:** The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

# Section 14: Transport information

14.1. UN number

UN number: UN1133

14.2. UN proper shipping name

Shipping name: ADHESIVES

(ETHYL ACETATE)

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: |||

GUN A NAIL EXTRA

Page: 8

Marine pollutant: No

# 14.5. Environmental hazards

Environmentally hazardous: No

# 14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 3

# Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# 15.2. Chemical Safety Assessment

# Section 16: Other information

### Other information

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	453/2010.
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	EUH066: Repeated exposure may cause skin dryness or cracking.
	H225: Highly flammable liquid and vapour.
	H304: May be fatal if swallowed and enters airways.
	H315: Causes skin irritation.
	H319: Causes serious eye irritation.
	H336: May cause drowsiness or dizziness.
	H411: Toxic to aquatic life with long lasting effects.
	H412: Harmful to aquatic life with long lasting effects.
	R11: Highly flammable.
	R36: Irritating to eyes.
	R38: Irritating to skin.
	R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic
	environment.
	R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the
	aquatic environment.
	R65: Harmful: may cause lung damage if swallowed.
	R66: Repeated exposure may cause skin dryness or cracking.
	R67: Vapours may cause drowsiness and dizziness.
Legend to abbreviations:	PNEC = predicted no effect level
	DNEL = derived no effect level
	LD50 = median lethal dose
	LC50 = median lethal concentration
	EC50 = median effective concentration

GUN A NAIL EXTRA

Page: 9

IC50 = median inhibitory concentration

dw = dry weight

bw = body weight

cc = closed cup

oc = open cup

MUS = mouse

GPG = guinea pig RBT = rabbit

HAM = hamster

HMN = human

MAM = mammal

PGN = pigeon

IVN = intravenous

SCU = subcutaneous

SKN = skin

DRM = dermal

OCC = ocular/corneal

PCP = phycico-chemical properties

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.